



- Designed for 15,000+ GVW trucks with ground clearances greater than 44 in.
- Works with 96 in. wide dump bodies
- Rugged 6 in. or 9 in. auger with continuous flighting to discharge at the extreme left or right end
- Mounts below dump body tailgate

Highlights

- Independent hydraulic control of auger and spinner
- Direct drive higher performance and lower maintenance
- 18 in. poly spin disc broadcasts up tp 40 ft.
- Available with standard or extreme left or right discharge
-) Stainless steel or carbon steel construction
- Stabilizer kit keeps spinner parallel to the road at all dump angles
- Tailgate shields
- Made in the USA

Specifications

| Size | 96 in. width |
|-----------------|---|
| Conveyor | SBD-6: 6 in. auger with continuous flighting SBD-9: 9 in. auger with continuous flighting |
| Drive | Hydrualic |
| Weight Empty | SBD-6: 540 lbs. SBD-9: 600 lbs. |
| Construction | 7 gauge carbon steel or 10 gauge stainless steel |
| Spread Width | 4–40 ft. |
| Safety Features | Hydrualic safety interlock |
| Warranty | 1 year |
| Accessories | Dual flow control valve controller, central hydraulic hose kit, central hydraulic 7 gallon tank kit |
| Controller | Purchased separately |

